

Fittings / LED Battens

40W Dura LED Anti Corrosive Batten - 4000K, Double 1200mm (4ft)



The Dura LED Anti Corrosive Batten is one of BELL's flagship Luminaires. This fully enclosed luminaire comes with stainless steel diffuser clips, ideal for exterior lighting projects that are open to the elements.

- The Smart Replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Injection moulded polycarbonate body - suitable for food environments
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Stainless steel clips & suspension brackets
- Tool-free termination

Technical Specification

| | |
|---------------------|-------|
| Product Code | 06728 |
|---------------------|-------|

Reference

| | |
|------------------|---------|
| Guarantee | 7 Years |
|------------------|---------|

| | |
|------------|---------------|
| EAN | 5013588067285 |
|------------|---------------|

| | |
|-----------------------|----------|
| Commodity Code | 94054099 |
|-----------------------|----------|

| | |
|--------------------------|----|
| Country Of Origin | CN |
|--------------------------|----|

| | |
|--------------------|----------|
| UNSPSC Code | 39111544 |
|--------------------|----------|

Technical Specification

| | |
|--------------------------------|---------|
| Volts (V) | 220-240 |
| Watts (W) | 40 |
| Colour Temp (K) | 4000 |
| Dimmable? | 0 |
| Lumens (lm) | 5550 |
| Candelas (cd) | 1,600 |
| Life Hours | 50,000 |
| Beam Angle | 128° |
| CRI (Ra) | 85 |
| Switching Cycles | 25,000 |
| Frequency (Hz) | 50/60 |
| LED Drive Current | 1,080 |
| Energy Consumption (kWh/1000h) | 40 |
| IP Rating | IP65 |

Dimensions

| | |
|-------------|-------|
| Height (mm) | 90 |
| Width (mm) | 125 |
| Length (mm) | 1,263 |

Packaging Information

| | |
|---------------------------|---------|
| Single Carton Height (mm) | 9.5 |
| Single Carton Width (mm) | 13.5 |
| Single Carton Depth (mm) | 126.5 |
| Individual Volume | 0.01622 |
| Outer Box Qty | 6 |
| Outer Box Height (mm) | 21.5 |
| Outer Box Width (mm) | 31 |
| Outer Box Depth (mm) | 129 |
| Outer Box CMB | 0.08598 |