

Fittings / LED Battens

20W Ultra LED Integrated Batten - 4000K, Single Emergency with Microwave Sensor 1230mm (4ft)



The Ultra Batten is a versatile general-purpose luminaire. With a sleek look, this Ultra Batten is an ideal candidate for office, classroom and corridor installations. Offered in 4, 5 & 6ft lengths, and boasting a 7 year guarantee with a 2 year on site warranty.

- The smart replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Tool-free termination
- Integrated controls
- Shatterproof

Technical Specification

| | |
|---------------------|-------|
| Product Code | 10203 |
|---------------------|-------|

Reference

| | |
|------------------|---------|
| Guarantee | 7 Years |
|------------------|---------|

| | |
|------------|---------------|
| EAN | 5013588102030 |
|------------|---------------|

| | |
|-----------------------|----------|
| Commodity Code | 94054099 |
|-----------------------|----------|

| | |
|--------------------------|----|
| Country Of Origin | CN |
|--------------------------|----|

| | |
|--------------------|----------|
| UNSPSC Code | 39111544 |
|--------------------|----------|

Technical Specification

| | |
|--------------------------------|---------|
| Volts (V) | 220-240 |
| Watts (W) | 20 |
| Colour Temp (K) | 4000 |
| Dimmable? | 0 |
| Lumens (lm) | 2850 |
| Candelas (cd) | 650 |
| Life Hours | 50,000 |
| Beam Angle | 156° |
| CRI (Ra) | 85 |
| Switching Cycles | 25,000 |
| Frequency (Hz) | 50/60 |
| LED Drive Current | 480 |
| Energy Consumption (kWh/1000h) | 20 |
| IP Rating | IP20 |

Dimensions

| | |
|-------------|-------|
| Height (mm) | 82 |
| Width (mm) | 69 |
| Length (mm) | 1,230 |

Packaging Information

| | |
|---------------------------|---------|
| Single Carton Height (mm) | 8.6 |
| Single Carton Width (mm) | 7.4 |
| Single Carton Depth (mm) | 123.6 |
| Individual Volume | 0.00787 |
| Outer Box Qty | 6 |
| Outer Box Height (mm) | 21 |
| Outer Box Width (mm) | 25 |
| Outer Box Depth (mm) | 125 |
| Outer Box CMB | 0.07 |