

## Fittings / LED Battens

### 60W Ultra LED Integrated Batten - 4000K, Double with Microwave Sensor + Corridor Dim Function 1530mm (5ft)



The Ultra Batten is a versatile general-purpose luminaire. With a sleek look, this Ultra Batten is an ideal candidate for office, classroom and corridor installations. Offered in 4, 5 & 6ft lengths, and boasting a 7 year guarantee with a 2 year on site warranty.

- The smart replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Tool-free termination
- Integrated controls
- Shatterproof

## Technical Specification

|                     |       |
|---------------------|-------|
| <b>Product Code</b> | 10222 |
|---------------------|-------|

### Reference

|                  |         |
|------------------|---------|
| <b>Guarantee</b> | 7 Years |
|------------------|---------|

|            |               |
|------------|---------------|
| <b>EAN</b> | 5013588102221 |
|------------|---------------|

|                       |          |
|-----------------------|----------|
| <b>Commodity Code</b> | 94054099 |
|-----------------------|----------|

|                          |    |
|--------------------------|----|
| <b>Country Of Origin</b> | CN |
|--------------------------|----|

|                    |          |
|--------------------|----------|
| <b>UNSPSC Code</b> | 39111544 |
|--------------------|----------|

## Technical Specification

|                                |         |
|--------------------------------|---------|
| Volts (V)                      | 220-240 |
| Watts (W)                      | 60      |
| Colour Temp (K)                | 4000    |
| Dimmable?                      | 0       |
| Lumens (lm)                    | 7600    |
| Candelas (cd)                  | 2,000   |
| Life Hours                     | 50,000  |
| Beam Angle                     | 128°    |
| CRI (Ra)                       | 85      |
| Switching Cycles               | 25,000  |
| Frequency (Hz)                 | 50/60   |
| LED Drive Current              | 1,440   |
| Energy Consumption (kWh/1000h) | 60      |
| IP Rating                      | IP20    |

## Dimensions

|             |       |
|-------------|-------|
| Height (mm) | 82    |
| Width (mm)  | 109   |
| Length (mm) | 1,530 |

## Packaging Information

|                           |         |
|---------------------------|---------|
| Single Carton Height (mm) | 8.6     |
| Single Carton Width (mm)  | 11.4    |
| Single Carton Depth (mm)  | 153.6   |
| Individual Volume         | 0.01506 |
| Outer Box Qty             | 4       |
| Outer Box Height (mm)     | 25      |
| Outer Box Width (mm)      | 21      |
| Outer Box Depth (mm)      | 155     |
| Outer Box CMB             | 0.08    |