



Fittings / LED Battens

50W Ultra LED Integrated Batten - 4000K, Single 1795mm (6ft)



The Ultra Batten is a versatile general-purpose luminaire. With a sleek look, this Ultra Batten is an ideal candidate for office, classroom and corridor installations. Offered in 4, 5 & 6ft lengths, and boasting a 7 year guarantee with a 2 year on site warranty.

- The smart replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Tool-free termination
- Integrated controls
- Shatterproof

Technical Specification

Product Code	10224	

Reference

Guarantee	7 Years
EAN	5013588102245
Commodity Code	94054099
Country Of Origin	CN
UNSPSC Code	39111544









Technical Specification

Watts (W) 50 Colour Temp (K) 4000 Dimmable? 0 Lumens (Im) 6350 Candelas (cd) 1,500 Life Hours 50,000 Beam Angle 116° CRI (Ra) 85 Switching Cycles 25,000 Frequency (Hz) 50/60 LED Drive Current 1,320 Energy Consumption (kWh/1000h) 50 IP Rating IP20 Dimensions B2 Width (mm) 82 Width (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Width (mm) 20 Outer Box Depth (mm) 182 Outer Box CMB 0.06552	Volts (V)	220-240
Dimmable? 0	Watts (W)	50
Lumens (Im) 6350 Candelas (cd) 1,500 Life Hours 50,000 Beam Angle 116° CRI (Ra) 85 Switching Cycles 25,000 Frequency (Hz) 50/60 LED Drive Current 1,320 Energy Consumption (kWh/1000h) 50 IP Rating IP20 Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Colour Temp (K)	4000
Candelas (cd) 1,500 Life Hours 50,000 Beam Angle 116° CRI (Ra) 85 Switching Cycles 25,000 Frequency (Hz) 50/60 LED Drive Current 1,320 Energy Consumption (kWh/1000h) 50 IP Rating IP20 Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Depth (mm) 182	Dimmable?	0
Life Hours 50,000 Beam Angle 116° CRI (Ra) 85 Switching Cycles 25,000 Frequency (Hz) 50/60 LED Drive Current 1,320 Energy Consumption (kWh/1000h) 50 IP Rating IP20 Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Lumens (lm)	6350
Beam Angle 116° CRI (Ra) 85 Switching Cycles 25,000 Frequency (Hz) 50/60 LED Drive Current 1,320 Energy Consumption (kWh/1000h) 50 IP Rating IP20 Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Candelas (cd)	1,500
CRI (Ra) 85 Switching Cycles 25,000 Frequency (Hz) 50/60 LED Drive Current 1,320 Energy Consumption (kWh/1000h) 50 IP Rating IP20 Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Width (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Life Hours	50,000
Switching Cycles 25,000 Frequency (Hz) 50/60 LED Drive Current 1,320 Energy Consumption (kWh/1000h) 50 IP Rating IP20 Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Width (mm) 20 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Beam Angle	116°
Frequency (Hz) 50/60 LED Drive Current 1,320 Energy Consumption (kWh/1000h) 50 IP Rating IP20 Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Width (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	CRI (Ra)	85
LED Drive Current1,320Energy Consumption (kWh/1000h)50IP RatingIP20DimensionsHeight (mm)82Width (mm)69Length (mm)1,795Packaging InformationSingle Carton Height (mm)8.6Single Carton Width (mm)7.4Single Carton Depth (mm)180Individual Volume0.01146Outer Box Qty4Outer Box Height (mm)18Outer Box Width (mm)20Outer Box Depth (mm)182	Switching Cycles	25,000
Energy Consumption (kWh/1000h) 50 IP Rating IP20 Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Frequency (Hz)	50/60
Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	LED Drive Current	1,320
Dimensions Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Energy Consumption (kWh/1000h)	50
Height (mm) 82 Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	IP Rating	IP20
Width (mm) 69 Length (mm) 1,795 Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Dimensions	
Length (mm) 1,795 Packaging Information Single Carton Height (mm) Single Carton Width (mm) 7.4 Single Carton Depth (mm) Individual Volume Outer Box Qty Outer Box Height (mm) Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Height (mm)	82
Packaging Information Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Width (mm)	69
Single Carton Height (mm) 8.6 Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Length (mm)	1,795
Single Carton Width (mm) 7.4 Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Packaging Information	
Single Carton Depth (mm) 180 Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Single Carton Height (mm)	8.6
Individual Volume 0.01146 Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Single Carton Width (mm)	7.4
Outer Box Qty 4 Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Single Carton Depth (mm)	180
Outer Box Height (mm) 18 Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Individual Volume	0.01146
Outer Box Width (mm) 20 Outer Box Depth (mm) 182	Outer Box Qty	4
Outer Box Depth (mm) 182	Outer Box Height (mm)	18
	Outer Box Width (mm)	20
Outer Box CMB 0.06552	Outer Box Depth (mm)	182
	Outer Boy CMR	0.06552

E: sales@belllighting.co.uk **T:** 01924 893380

