



Fittings / LED Battens

50W Ultra LED Integrated Batten - 4000K, Single Emergency with Microwave Sensor 1795mm (6ft)



The Ultra Batten is a versatile general-purpose luminaire. With a sleek look, this Ultra Batten is an ideal candidate for office, classroom and corridor installations. Offered in 4, 5 & 6ft lengths, and boasting a 7 year guarantee with a 2 year on site warranty.

- The smart replacement for Single/Twin Fluorescent T8 and T5 Fixtures
- Special high light transmission frosted polycarbonate diffuser for smooth uniform lighting
- Tool-free termination
- Integrated controls
- Shatterproof

Technical Specification

Product Code	10227

Reference

Guarantee	7 Years
EAN	5013588102276
Commodity Code	94054099
Country Of Origin	CN
UNSPSC Code	39111544









Technical Specification

Volts (V)	220-240
Watts (W)	50
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	6350
Candelas (cd)	1,500
Life Hours	50,000
Beam Angle	116°
CRI (Ra)	85
Switching Cycles	25,000
Frequency (Hz)	50/60
LED Drive Current	1,320
Energy Consumption (kWh/1000h)	50
IP Rating	IP20
Dimensions	
Height (mm)	82
Width (mm)	69
Length (mm)	1,795
Packaging Information	
rackaging information	
Single Carton Height (mm)	8.6
	8.6 7.4
Single Carton Height (mm)	
Single Carton Height (mm) Single Carton Width (mm)	7.4
Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm)	7.4 180
Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Individual Volume	7.4 180 0.01146
Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Individual Volume Outer Box Qty	7.4 180 0.01146 4
Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Individual Volume Outer Box Qty Outer Box Height (mm)	7.4 180 0.01146 4 18
Single Carton Height (mm) Single Carton Width (mm) Single Carton Depth (mm) Individual Volume Outer Box Qty Outer Box Height (mm) Outer Box Width (mm)	7.4 180 0.01146 4 18 20

E: sales@belllighting.co.uk **T:** 01924 893380

