

Fittings / Downlights

6W Firestay LED Integrated Fixed Downlight, Incl White & Satin Bezel - 6000K - Tool Free Termination Oversized Fitting



The Firestay LED Oversized Downlight does exactly what it says on the tin. The oversized bezel gives users the opportunity to 'make good' on large holes when switching from outdated CFL technology.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist ceiling systems (certification pending)
- IP65
- Part B/C/E compliant
- White bezel & magnetic satin bezel
- Part L compliant

Technical Specification

Product Code	10517
---------------------	-------

Reference

Guarantee	3 Years
EAN	5013588105178
Commodity Code	94054099
Country Of Origin	CN
UNSPSC Code	39111515

Technical Specification

Volts (V)	220-240
Watts (W)	6
Colour Temp (K)	6000
Dimmable?	1
Lumens (lm)	610
Candelas (cd)	1,150
Life Hours	35,000
Beam Angle	40°
CRI (Ra)	85
Switching Cycles	10,000
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	6
IP Rating	IP65

Dimensions

Width (mm)	70
Depth (mm)	64.3
Diameter (mm)	93.4
Downlight Cut Out (mm)	70-80

Packaging Information

Single Carton Height (mm)	8.4
Single Carton Width (mm)	10.2
Single Carton Depth (mm)	9.8
Single Carton Weight (KG)	0.33
Individual Volume	0.00084
Inner Box Qty	10
Outer Box Qty	20
Outer Box Height (mm)	52
Outer Box Width (mm)	23.5
Outer Box Depth (mm)	20
Outer Box CMB	0.02444