

Fittings / Downlights

Fire Rated MV/LV Showerlight - Antique Brass



The Firestay Non Integrated Downlight gives you the freedom to choose your lamp without the need to replace the complete fitting. Available as Fixed, Centre Tilt & IP65 Showerlight with a choice of finishes and accessories.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist ceiling systems
- Part B/C/E compliant
- Part L compliant with BELL Halo Elite/Halo Glass LED GU10
- Fixed / Centre Tilt / Showerlight IP65 Downlights
- Suitable for 240V lamps (GU10 lamp holder included)

Technical Specification

| | |
|--------------|-------|
| Product Code | 10653 |
|--------------|-------|

Reference

| | |
|----------------|---------------|
| Guarantee | 5 Years |
| EAN | 5013588106533 |
| Commodity Code | 94054099 |
| UNSPSC Code | 39111515 |

Technical Specification

| | |
|----------------|------|
| Volts (V) | 240 |
| Cap | GU10 |
| Dimmable? | 0 |
| Frequency (Hz) | 50 |
| IP Rating | IP65 |

Dimensions

| | |
|------------------------|-----|
| Height (mm) | 100 |
| Width (mm) | 93 |
| Depth (mm) | 96 |
| Length (mm) | 134 |
| Diameter (mm) | 85 |
| Downlight Cut Out (mm) | 68 |

Packaging Information

| | |
|---------------------------|---------|
| Single Carton Height (mm) | 7.8 |
| Single Carton Width (mm) | 10.5 |
| Single Carton Depth (mm) | 8.9 |
| Single Carton Weight (KG) | 0.71 |
| Individual Volume | 0.00073 |
| Outer Box Qty | 50 |
| Outer Box Height (mm) | 41.5 |
| Outer Box Width (mm) | 48 |
| Outer Box Depth (mm) | 22.5 |
| Outer Box CMB | 0.04482 |