

## Fittings / Downlights

### Fire Rated MV/LV Downlight - Satin Nickel



The Firestay Non Integrated Downlight gives you the freedom to choose your lamp without the need to replace the complete fitting. Available as Fixed, Centre Tilt & IP65 Showerlight with a choice of finishes and accessories.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist ceiling systems
- Part B/C/E compliant
- Part L compliant with BELL Halo Elite/Halo Glass LED GU10
- Fixed / Centre Tilt / Showerlight IP65 Downlights
- Suitable for 240V lamps (GU10 lamp holder included)

## Technical Specification

<b>Product Code</b>	10661
---------------------	-------

### Reference

<b>Guarantee</b>	5 Years
<b>EAN</b>	5013588106618
<b>Commodity Code</b>	94054099
<b>Country Of Origin</b>	CN
<b>UNSPSC Code</b>	39111515

### Technical Specification

<b>Volts (V)</b>	240
<b>Cap</b>	GU10
<b>Dimmable?</b>	0
<b>Frequency (Hz)</b>	50
<b>IP Rating</b>	IP20

## Dimensions

Height (mm)	98
Width (mm)	93
Depth (mm)	94
Length (mm)	134
Diameter (mm)	85
Downlight Cut Out (mm)	68

## Packaging Information

Single Carton Height (mm)	7.8
Single Carton Width (mm)	10.5
Single Carton Depth (mm)	8.9
Single Carton Weight (KG)	0.67
Individual Volume	0.00073
Outer Box Qty	50
Outer Box Height (mm)	41.5
Outer Box Width (mm)	46.5
Outer Box Depth (mm)	22.5
Outer Box CMB	0.04342