



## Fittings / Downlights

## 16W Arial Pro Downlight IP65 - CCT



The Arial Pro LED Downlight is a sleek looking luminaire designed to replace cumbersome CFL fittings. With a 7 year guarantee across both the IP44 & IP65 range, the Arial Pro can be installed in a variety of applications with the confidence of knowing this product will stand the test of time.

- Switchable colour temperature 3000/4000/6000K
- Ideal for home and office environments
- Equivalent up to 2x26W fluorescent
- Anti-glare

**Product Code** 

• Tool Free - Plug & Play

## **Technical Specification**

Reference	
Guarantee	7 Years
EAN	5013588109541
Commodity Code	94054099
Country Of Origin	CN
UNSPSC Code	39111515

10954









## **Technical Specification**

Volts (V)	220-240
Watts (W)	16
Colour Temp (K)	3000/4000/6000
Dimmable?	0
Lumens (lm)	1660
Life Hours	50,000
Beam Angle	90°
CRI (Ra)	85
Switching Cycles	25,000
Frequency (Hz)	50/60
LED Drive Current	400
Energy Consumption (kWh/1000h)	16
IP Rating	IP65
Dimensions	
Dimensions Height (mm)	102
	102 190
Height (mm)	
Height (mm)  Diameter (mm)	190
Height (mm)  Diameter (mm)  Downlight Cut Out (mm)	190
Height (mm)  Diameter (mm)  Downlight Cut Out (mm)  Packaging Information	190 160-170
Height (mm)  Diameter (mm)  Downlight Cut Out (mm)  Packaging Information  Single Carton Height (mm)	190 160-170 12.6
Height (mm)  Diameter (mm)  Downlight Cut Out (mm)  Packaging Information  Single Carton Height (mm)  Single Carton Width (mm)	190 160-170 12.6 20
Height (mm)  Diameter (mm)  Downlight Cut Out (mm)  Packaging Information  Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)	190 160-170 12.6 20 20
Height (mm)  Diameter (mm)  Downlight Cut Out (mm)  Packaging Information  Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (KG)	190 160-170 12.6 20 20 0.65
Height (mm)  Diameter (mm)  Downlight Cut Out (mm)  Packaging Information  Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (KG)  Individual Volume	190 160-170 12.6 20 20 0.65 0.00504
Height (mm)  Diameter (mm)  Downlight Cut Out (mm)  Packaging Information  Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (KG)  Individual Volume  Outer Box Qty	190 160-170 12.6 20 20 0.65 0.00504
Height (mm)  Diameter (mm)  Downlight Cut Out (mm)  Packaging Information  Single Carton Height (mm)  Single Carton Width (mm)  Single Carton Depth (mm)  Single Carton Weight (KG)  Individual Volume  Outer Box Qty  Outer Box Height (mm)	190 160-170 12.6 20 20 0.65 0.00504 12 40



