



Fittings / LED Floodlights

100W Skyline Slim+ Asymmetric LED Floodlight -4000K



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body
- Fully encapsulated IP65 TUV certified driver
- PIR Over-ride function
- Average 8M detection range for PIR Floods
- Separately tested IP65 PIR

Technical Specification

Product Code	10977
Reference	
Guarantee	5 Years
EAN	5013588109770
Commodity Code	9405423990
Country Of Origin	CN
UNSPSC Code	39111626

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 1/15/2024 1:19:15 PM





Technical Specification

Volts (V)	240
Watts (W)	100
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	11000
Life Hours	50,000
CRI (Ra)	80
Switching Cycles	25,000
Frequency (Hz)	50/60
LED Drive Current	930
Energy Consumption (kWh/1000h)	100
IP Rating	IP65
Dimensions	
Height (mm)	315
Width (mm)	277
Depth (mm)	60
Packaging Information	
Single Carton Height (mm)	32.3
Single Carton Width (mm)	28
Single Carton Depth (mm)	7
Individual Volume	0.00633
Outer Box Qty	4
Outer Box Height (mm)	35.3
Outer Box Width (mm)	30.4
Outer Box Depth (mm)	29.6

E: sales@belllighting.co.uk **T:** 01924 893380

www.belllighting.co.uk



This document is uncontrolled if printed, all information is subject to change. Generated on 1/15/2024 1:19:15 PM