

## Fittings / LED Floodlights

### 30W Skyline Slim+ PIR LED Floodlight - 4000K



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body
- Fully encapsulated IP65 TUV certified driver
- PIR Over-ride function
- Average 8M detection range for PIR Floods
- Separately tested IP65 PIR

## Technical Specification

|              |       |
|--------------|-------|
| Product Code | 10987 |
|--------------|-------|

### Reference

|                   |               |
|-------------------|---------------|
| Guarantee         | 5 Years       |
| EAN               | 5013588109879 |
| Commodity Code    | 9405423990    |
| Country Of Origin | CN            |
| UNSPSC Code       | 39111626      |

## Technical Specification

|                                |        |
|--------------------------------|--------|
| Volts (V)                      | 240    |
| Watts (W)                      | 30     |
| Colour Temp (K)                | 4000   |
| Dimmable?                      | 0      |
| Lumens (lm)                    | 3600   |
| Life Hours                     | 50,000 |
| Beam Angle                     | 110°   |
| CRI (Ra)                       | 80     |
| Switching Cycles               | 25,000 |
| Frequency (Hz)                 | 50/60  |
| LED Drive Current              | 305    |
| Energy Consumption (kWh/1000h) | 30     |
| IP Rating                      | IP65   |

## Dimensions

|             |     |
|-------------|-----|
| Height (mm) | 200 |
| Width (mm)  | 137 |
| Depth (mm)  | 72  |

## Packaging Information

|                           |         |
|---------------------------|---------|
| Single Carton Height (mm) | 20.3    |
| Single Carton Width (mm)  | 13.9    |
| Single Carton Depth (mm)  | 8.6     |
| Individual Volume         | 0.00243 |
| Outer Box Qty             | 12      |
| Outer Box Height (mm)     | 23.3    |
| Outer Box Width (mm)      | 43.8    |
| Outer Box Depth (mm)      | 36.8    |