



Fittings / LED Floodlights

100W Skyline Slim+ LED Floodlight - 4000K



The Skyline Slim+ LED Floodlight is suitable for a wide range of applications. Available in a vast range of wattages, this low energy floodlight is ideal for any lighting project, big or small.

- Marine Grade Aluminium body
- Fully encapsulated IP65 TUV certified driver

Technical Specification

5 Years
5013588109909
9405423990
CN

10990

39111626

E: sales@belllighting.co.uk T: 01924 893380



Product Code

UNSPSC Code





Technical Specification

Volts (V)	240
Watts (W)	100
Colour Temp (K)	4000
Dimmable?	0
Lumens (lm)	12000
Life Hours	50,000
Beam Angle	110°
CRI (Ra)	80
Switching Cycles	25,000
Frequency (Hz)	50/60
LED Drive Current	930
Energy Consumption (kWh/1000h)	100
IP Rating	IP65
Dimensions Height (mm)	318
Width (mm)	276
Depth (mm)	60
Packaging Information	
Single Carton Height (mm)	32.3
Single Carton Width (mm)	28
Single Carton Depth (mm)	7
Individual Volume	0.00633
Outer Box Qty	4
Outer Box Height (mm)	35.3
Outer Box Width (mm)	30.4
Outer Box Depth (mm)	29.6



