

112542

ShieldPRO Anti-glare 4CCT




FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt black & clear acrylic finish
- Constructed from steel & polycarbonate & acrylic
- Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- Fire rated to 30, 60 & 90 minutes
- It is suitable for covering with insulation 270mm
- I-Joist certified to 30 mins
- Steel open web joist certified to 30 mins
- IP65



SPEC DATA

Product Wattage:	5/7W
Product Lumen:	520
Lumen/W:	74
Kelvin:	2700/3000/4000/6000K
Energy Rating:	E
Dimmable:	Yes
Beam Angle:	60°
Power Factor:	0.9
SDCM:	6
CRI:	80
Lifetime (Hours):	30000
LED Brand:	Samsung
Driver Type:	Constant current 170mA
Inrush Current at Start Up:	10A
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	2KV
Operating Temp.:	-20 to 40 Degree
Cut out:	Ø75mm
Minimum Cavity Depth:	70mm
Product Weight (KG):	0.2362
Terminal Block:	3/6 way fast fit
Class:	2



ACCESSORIES

- 114580, ShieldPRO anti glare insert black
- 114581, ShieldPRO anti glare insert chrome
- 114582, ShieldPRO anti glare insert black nickel
- 114583, ShieldPRO anti glare insert gold