Xnightsbridge

DATASHEET



12DC25D

IP20 12V 25W DC Dimmable LED Driver - Constant Voltage

www.mlaccessories.co.uk

NET WEIGHT (KG) 0.11	MLA PART CODE	12DC25D
White Length - 128	DESCRIPTION	IP20 12V 25W DC Dimmable LED Driver - Constant Voltage
Length - 128	NET WEIGHT (KG)	0.11
DIMENSIONS (MM)	FINISH	White
II IPPRATING IPPO DISPLACEMENT FACTOR SVM 0.37 PST-LM 0.37 LIFE SPAN (HRS) DIMMABLE Trailing-edge only* INPUT VOLTAGE SECONDARY VOLTAGE DRIVER DRIVER DRIVER DRIVER WARRANTY WARRANTY WARRANTY WARRANTY WARRANTY WARRANTY WARRANTY BECONDARY (HELD ON FILE) II IP20 OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20-50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY TEMPERATURE (Tc) - 70°C WARRANT	DIMENSIONS (MM)	Height - 30
DISPLACEMENT FACTOR DISPLACEMENT FACTOR SVM 0.37 PST-LM 0.37 LIFE SPAN (HRS) DIMMABLE Trailing-edge only* INPUT VOLTAGE SECONDARY VOLTAGE DRIVER DRIVER DRIVER DRIVER TYPE - Constant Voltage MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY PULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY 3year(s) MANUFACTURED IN ACCORDANCE WITH DECLARATION OF CONFORMITY (HELD ON FILE) Yes	CONSTRUCTION	Construction - ABS
DISPLACEMENT FACTOR SVM 0.37 PST-LM 0.37 LIFE SPAN (HRS) DIMMABLE Trailing-edge only* INPUT VOLTAGE SECONDARY VOLTAGE DRIVER DRIVER	CLASS	II
DRIVER DRIVER	IP RATING	IP20
DRIVER DRIVER	DISPLACEMENT FACTOR	>0.9
LIFE SPAN (HRS) DIMMABLE Trailing-edge only* INPUT VOLTAGE SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY 3year(s) MANUFACTURED IN ACCORDANCE WITH EN 61347, EN 62493 ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	SVM	0.37
DIMMABLE INPUT VOLTAGE SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY MANUFACTURED IN ACCORDANCE WITH DECLARATION OF CONFORMITY (HELD ON FILE) Trailing-edge only* 230V 50Hz DRIVER DRIVER DRIVER DRIVER TYPE - Constant Voltage MAX. OUTPUT - 25W OUTPUT - 25W OUTPUT - 25W OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY Syear(s) MANUFACTURED IN ACCORDANCE WITH EN 61347, EN 62493 ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE)	PST-LM	0.37
INPUT VOLTAGE SECONDARY VOLTAGE 12V DRIVER TYPE - Constant Voltage MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY 3year(s) MANUFACTURED IN ACCORDANCE WITH EN 61347, EN 62493 ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	LIFE SPAN (HRS)	50,000
DRIVER TYPE - Constant Voltage MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY 3year(s) MANUFACTURED IN ACCORDANCE WITH EN 61347, EN 62493 ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) PRIVER TYPE - Constant Voltage MAX. OUTPUT - 25W OUTPUT - 25W OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY Yes	DIMMABLE	Trailing-edge only*
DRIVER TYPE - Constant Voltage MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY 3year(s) MANUFACTURED IN ACCORDANCE WITH EN 61347, EN 62493 ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) PORTUPIT - 25W OUTPUT - 20*50 OUTPUT - 25W OUTPUT - 25	INPUT VOLTAGE	230V 50Hz
MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 70°C WARRANTY 3year(s) MANUFACTURED IN ACCORDANCE WITH EN 61347, EN 62493 ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) WARRANTY Yes	SECONDARY VOLTAGE	12V
MANUFACTURED IN ACCORDANCE WITH ORIGIN OF MANUFACTURE DECLARATION OF CONFORMITY (HELD ON FILE) The state of the state o	DRIVER	MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 2080mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 84 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C
ORIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	WARRANTY	3year(s)
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	MANUFACTURED IN ACCORDANCE WITH	EN 61347, EN 62493
	ORIGIN OF MANUFACTURE	China
5055000570004	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
=AN 5055832978961	EAN	5055832978961

Date Created: 08/01/2024 14:51



