FT-45[™] ORDERING INFORMATION

FT-45[™] Feed Thru Modular Plug Crimp Tool



Cat. No.	Description	
30-495	FT-45 [™] Feed-Thru Modular Plug Crimp Too	
30-4951	FT-45 [™] Replacement Blade	

Cat 6a/6/5e Shielded Modular Plugs



Cat. No.	Description	Qty per pack
85-361	CAT5e Shielded RJ-45	25
85-365	CAT5e Shielded Feed-Thru RJ-45	25
85-368	CAT6A/6/5e Shielded Feed-Thru	25

Cat 6 Feed-Thru RJ-45 Modular Plugs



Cat. No.	Description	Qty pe pack
85-375	Cat 6 Feed-Thru Unshielded RJ-45	25
85-376	Cat 6 Feed-Thru Unshielded RJ-45	50
85-377	Cat 6 Feed-Thru Unshielded RJ-45	100

Cat 5e Feed-Thru RJ-45 Modular Plugs



OTHER PRODUCTS AVAILABLE

Cat. No.	Description	Qty per pack
85-370	Cat 5e Feed-Thru Unshielded RJ-45	25
85-371	Cat 5e Feed-Thru Unshielded RJ-45	50
85-372	Cat 5e Feed-Thru Unshielded RJ-45	100

Cat 6 RJ-45 Standard Modular Plugs and Strain Relief Boots



Cat No		Description	Qty per pack
85-3	646	Cat 5e RJ-45 Standard 8P8C	25
85-3	666	Cat 6 RJ-45 Standard 8P8C	25
85-3	80	Strain Relief Boots for Modular Plugs	25

Kinetic Super[™] Wire Stripper/Crimper Kit



Cat. No. Description

33-719 Kinetic Super[™] Wire Stripper/Crimper Kit (includes x25 UR-I 3 Wire Butt Splice IDCs)





Cat. No.	Description
45-165	UTP/STP/Coaxial Cable Stripper
45-605	PrepPRO [®] UTP/Coax Cable Stripper

Data T[®]-Cutter



Electrician's Scissors

Cat. No.Description35-088Electrician's Scissors

FOR ADDITIONAL INFORMATION ON OUR DATA RANGE PLEASE VISIT:

CE

WWW.IDEALIND.COM

IDEAL INDUSTRIES EMEA Unit 3, Europa Court, Europa Boulevard, Westbrook, Warrington, WA5 7TN, UK Tel.: +44 (0)1925 44 44 46 · Fax: +44 (0)1925 44 55 01 · sales@idealelectrical.eu

FT-45[™] FEED-THRU MODULAR PLUG SOLUTION



FEED-THRU MODULAR PLUGS



INTRODUCTION

The IDEAL Feed-Thru RJ-45 Modular Plugs and FT-45[™] Crimping Tool are designed to simplify and improve the consistency of cable to connector termination of CAT5e, CAT6 and CAT6A modular plugs to twisted pair cables.





FT-45 MODULAR PLUG CRIMP TOOL

The FT-45[™] is a simple, compact and highly effective crimp tool for installers and technicians that terminate RJ-45 connectors regularly.

- Quality Cleanly shears the excess conductors and leaves a smooth. flat finish
- Versatile Suitable with Feed-Thru, standard, shielded . or unshielded connectors (CAT5e, CAT6 or CAT6A)
- Heavy duty Cutting blade that will last for over 2,000 cuts
- Ergonomic Reduced hand force compared to traditional crimp tools
- Compact Easily fits in your pocket and lightens the tool bag load
- Easy to use 568A & 568B wiring scheme marked on the tool
- Easily maintained Replaceable cutting blades available
- Patented design Patent pending design requires less than ½ of the mechanical force to crimp connectors. No ratchet needed.



SIMPLIFIED MODULAR PLUG TERMINATIONS

Anyone who has assembled traditional standard or multi-piece modular plugs knows it is a time consuming and often error-prone process.

Reduces errors - Wires can be easily verified before trimming



- Easy to use Conductors do not need to be pre-trimmed to a specific length. Traditionally conductors that are trimmed too long may lead to excessive untwisting of the conductors or the cable jacket not being secured under the strain relief tab.
- Improved wire stability 3 prong contacts into every wire for more conductive contact points Many other RJ-45 modular plugs only have 2 prong contacts which reduces wire penetration.

Compatible with Cat5e / Cat6 / Cat6A

Standard Feed-Thru Shielded RJ-45



3 pin IDC contact, 50µ gold plated over 150µ nickel. Secured in place - no loose pins in the package.

Jacket seats past strain relief tab

Large Diameter

CAT6A/6/5e

Pair twists

maintained within

6.4 mm of contact







Step 7: Place assembly Squeeze handle closed



jacket base, and align in order. Trim ends flat. Step 4: Slide cable into



connector until fully seated. For Shielded: until foil enters back end of connector. Verify wiring order.

Step 5: Shielded only:

base of strain relief

(optional) or cut off.

Wrap drain wire around

Step 1: Remove 25 - 40

For Shielded: Ensure foil

Step 2: Remove centre

Step 3: Untwist pairs to

is left intact and fold over

mm of jacket.

foil to jacket base

spline if present.











Charles -