

COMBI, COMBI 407 and COMBI 607



by WISKA

COMBI 407



Protection Class IP66/67
Glow wire test 750 °C
Temperature range -30 °C · 100 °C
Installation temp -5 °C · 60 °C
Voltage 690V
Ampere 32A
Terminals/poles 4 mm²
Advice 7 x 20mm threaded entries / 1 x 25mm knockout
Material Polypropylene, Gasket: TPE





COMBI 407 (Light Grey)



COMBI 407 (Black)

COMBI 407, Junction Box

| Type | Light Grey | Black | White |  (mm) | LxBxH external (mm) |  |
|------------------------|------------|----------|----------|--|---------------------|---|
| COMBI 407/empty | 10105595 | 10105601 | 10105598 | 3 · 12 | 95 x 95 x 60 | 5 |
| COMBI 407/5 | 10105596 | 10105602 | 10105599 | 3 · 12 | 95 x 95 x 60 | 5 |
| COMBI 407/4SDKF5 (24A) | 10106191 | 10106192 | 10106193 | 3 · 12 | 95 x 95 x 60 | 5 |



by WISKA

COMBI 607



Protection Class IP66/67
Glow wire test 750 °C
Temperature range -30 °C · 100 °C
Installation temp -5 °C · 60 °C
Voltage 690V
Ampere 41A
Terminals/poles 6 mm²
Advice 7 x 25mm threaded entries
Material Polypropylene, Gasket: TPE





COMBI 607 (Light Grey)



COMBI 607 (Black)

COMBI 607, junction Box

| Type | Light Grey | Black | White |  (mm) | LxBxH external (mm) |  |
|------------------|------------|----------|----------|--|---------------------|---|
| COMBI 607/empty | 10060531 | 10060648 | 10060533 | 3 · 17 | 110 x 110 x 66 | 3 |
| COMBI 607/5 | 10061778 | 10061779 | 10060534 | 3 · 17 | 110 x 110 x 66 | 3 |
| DIN Rail Kit 607 | 10060361 | | | | | 1 |

For  Earthing Bars please turn the page...