

# Aquaendure

## Aqua Endure 18-36W LED CCT Power Switch Anti-Ligature Bulkhead

### Part Code: 70035

The Aqua Endure is an anti-ligature and anti-vandal bulkhead, perfect for use in areas where a fitting's durability is paramount.

- Genuine replacement for 38W & 70W bulkheads
- Suitable for custodial and secure healthcare applications
- Designed with safety as a priority
- High impact polycarbonate lens
- CCT 3000/4000/6000K



**10 Year**  
Guarantee



**220/240**  
Volts



**100,000**  
Life Hours



**3/4/6K**  
Colour Temperatures



# Aquaendure



<b>Product Category</b>	Fittings / Fittings
<b>Application</b>	Anti-Ligature Bulkhead
<b>Product Warranty</b>	10 Years
<b>EAN</b>	5013588700359
<b>Commodity Code</b>	9405423990
<b>Country of Origin</b>	CN

## Technical Specification

Watts (W)	18-36
Equivalent Watts (W)	67
Volts (V)	220/240
Colour Temp (K)	3000/4000/6000
Lumens (lm)	18W = 2847 (3000K) / 3027 (4000K) / 3111 (6000K) - 23W = 3637 (3000K) / 3868 (4000K) / 3975 (6000K) - 28W = 4428 (3000K) / 4708 (4000K) / 4839 (6000K) - 36W = 5680 (3000K) / 6102 (4000K) / 6260 (6000K)
Lumens per Watt (lm/W)	158-173
CRI (ra)	80
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	36
Life Hours	100000
Switching Cycles	50000
Impact Protection	IK20
IP Rating	IP66

## Packaging Information

Height (mm)	110
Diameter (mm)	400
Individual Product Weight (kg)	3.62
Single Carton Height (mm)	165
Single Carton Width (mm)	447
Single Carton Depth (mm)	447
Single Carton Weight (kg)	4.79
Individual Volume	0.032968485
Outer Box Qty	2
Outer Box Height (mm)	470
Outer Box Width (mm)	470
Outer Box Depth (mm)	365
Outer Box Weight (kg)	10.74
Outer Box Volume	0.0806285

# Aquaendure

Additional Information	
Beam Angle	117°