



Aqua Endure 18-36W LED CCT Power Switch Anti-Ligature Bulkhead with Microwave Corridor Dim

Part Code: 70037

The Aqua Endure is an anti-ligature and anti-vandal bulkhead, perfect for use in areas where a fitting's durability is paramount.

- Genuine replacement for 38W & 70W bulkheads
- Suitable for custodial and secure healthcare applications
- Designed with safety as a priority
- High impact polycarbonate lens
- CCT 3000/4000/6000K













Email: technical@belllighting.co.uk **Telephone:** 01924 893380

www.belllighting.co.uk

BELLlighting

Aquaendure

<		

Fittings / Fittings
Anti-Ligature Bulkhead
10 Years
5013588700373
9405423990
CN

Technical Specification		
Watts (W)	18-36	
Equivalent Watts (W)	67	
Volts (V)	220/240	
Colour Temp (K)	3000/4000/6000	
Lumens (Im)	18W = 2847 (3000k) / 3027 (4000k) / 3111 (6000k) - 23W = 3637 (3000k) / 3686 (4000k) / 3975 (6000k) - 28W = 4428 (3000k) / 4708 (4000k) / 4839 (6000k) - 68W = 5680 (3000k) / 6102 (4000k) / 6260 (6000k)	
Lumens per Watt (lm/W)	158-173	
CRI (ra)	80	
Frequency (Hz)	50/60	
Energy Consumption (kWh/1000h)	36	
Life Hours	100000	
Switching Cycles	50000	
Impact Protection	IK20	
IP Rating	IP66	

Packaging Information		
Height (mm)	110	
Diameter (mm)	400	
Individual Product Weight (kg)	3.63	
Single Carton Height (mm)	165	
Single Carton Width (mm)	447	
Single Carton Depth (mm)	447	
Single Carton Weight (kg)	4.8	
Individual Volume	0.032968485	
Outer Box Qty	2	
Outer Box Height (mm)	470	
Outer Box Width (mm)	470	
Outer Box Depth (mm)	365	
Outer Box Weight (kg)	10.76	
Outer Box Volume	0.0806285	

Email: technical@belllighting.co.uk **Telephone:** 01924 893380

www.belllighting.co.uk



Aquaendure

Additional Information			
Beam Angle	117°		

Email: technical@belllighting.co.uk **Telephone:** 01924 893380

www.belllighting.co.uk