

Aquaendure

Aqua Endure 18-36W LED CCT Power Switch Standard Anti-Ligature Bulkhead in Self-Test Emergency with Microwave Corridor Dim

Part Code: 70038

The Aqua Endure is an anti-ligature and anti-vandal bulkhead, perfect for use in areas where a fitting's durability is paramount.

- Genuine replacement for 38W & 70W bulkheads
- Suitable for custodial and secure healthcare applications
- Designed with safety as a priority
- High impact polycarbonate lens
- CCT 3000/4000/6000K



10 Year
Guarantee



220/240
Volts



100,000
Life Hours



3/4/6K
Colour Temperatures



Aquaendure



Product Category	Fittings / Fittings
Application	Anti-Ligature Bulkhead
Product Warranty	10 Years
EAN	5013588700380
Commodity Code	9405423990
Country of Origin	CN

Technical Specification

Watts (W)	18-36
Equivalent Watts (W)	67
Volts (V)	220/240
Colour Temp (K)	3000/4000/6000
Lumens (lm)	18W = 2847 (3000K) / 3027 (4000K) / 3111 (6000K) - 23W = 3637 (3000K) / 3868 (4000K) / 3975 (6000K) - 28W = 4428 (3000K) / 4708 (4000K) / 4839 (6000K) - 36W = 5680 (3000K) / 6102 (4000K) / 6260 (6000K)
Lumens per Watt (lm/W)	158-173
Emergency Lumen Output (lm)	242
CRI (ra)	80
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	36
Life Hours	100000
Switching Cycles	50000
Impact Protection	IK20
IP Rating	IP66

Packaging Information

Height (mm)	110
Diameter (mm)	400
Individual Product Weight (kg)	3.77
Single Carton Height (mm)	165
Single Carton Width (mm)	447
Single Carton Depth (mm)	447
Single Carton Weight (kg)	4.94
Individual Volume	0.032968485
Outer Box Qty	2
Outer Box Height (mm)	470
Outer Box Width (mm)	470
Outer Box Depth (mm)	365
Outer Box Weight (kg)	11.04
Outer Box Volume	0.0806285

Aquaendure

Additional Information	
Beam Angle	117°