

BODENN

The Bodenn is a robust, mains operated ground light which is constructed from marine grade stainless steel (316) and is IP67 rated, making it ideal for coastal areas. The plastic exterior is to be fitted into the ground and then the light simply screws in on top. It is ideal for lighting up paths and driveways. Can also be used as a decking light without using the plastic casing. Comes pre-wired with a 1.5m flex cable.



MARINE  
GRADE  
316L

IP67  
RATED

PRE-CABLE  
1.5M

2 YEAR WARRANTY

COB

IP67

A

IK08

- Constructed from marine grade stainless steel (316) & polycarbonate
- Min void: 90mm

CODE	DESCRIPTION	LAMP	K	LM	LM/W	DIMENSIONS	CUT OUT
78647	Bodenn IP67	1.3W LED module (COB)	3000	140	108	Proj: 2mm Dia: 45mm H: 92mm	Dia: 39mm
78646	Bodenn IP67	1.3W LED module (COB)	4000	140	108	Proj: 2mm Dia: 45mm H: 92mm	Dia: 39mm

HOXTON

The Hoxton recessed ground light is constructed from 304 stainless steel with a glass diffuser. This strong and sturdy fitting is IK08 and IP67. Its unique externally adjustable light source allows for it to be adjusted without the need to open the luminaire and compromise its IP status. Comes pre-wired with a 0.5m flex cable. Available in two sizes and two colour temperatures.



NEW  
PRODUCT

ADJUSTABLE  
LIGHT  
HEAD

IK08  
RATED

IP67  
RATED

PRE-CABLE  
0.5M

3 YEAR WARRANTY

COB

IP67

IK08

A

- Constructed from stainless steel (304) & glass
- Min void: 123mm



108mm

141mm

CODE	DESCRIPTION	LAMP	K	LM	LM/W	DIMENSIONS	CUT OUT
90962	Hoxton IP67	6W LED module (COB)	3000	500	83	Proj: 4.5mm H: 128mm Dia: 108mm	Dia: 102mm
79195	Hoxton IP67	6W LED module (COB)	4000	500	83	Proj: 4.5mm H: 128mm Dia: 108mm	Dia: 102mm
90963	Hoxton IP67	10.5W LED module (COB)	4000	1000	95	Proj: 4.5mm H: 158mm Dia: 141mm	Dia: 132.5