


Beacon LED Emergency Adjustable Downlight

Supplied c/w Remote Driver and Battery Pack

422



- LED Non-Maintained adjustable die-cast aluminium downlight
- 3 hour emergency output
- Power and green charge LED are discreetly incorporated within the head
- 120° beam angle



***	Escape route 2 metres wide (1 Lux minimum) *			
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	3.3	6.5	3.3	6.5
4	3.1	8.3	3.1	8.3
6	-	-	-	-

***	Open (Anti-Panic) area (0.5 Lux Minimum) **			
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	3.1	6.7	3.1	6.7
4	3.4	8.6	3.4	8.6
6	3.5	10	3.5	10

- * 1 lux minimum must be used for all marked emergency escape routes, to be measured down the centre line of the escape route itself
- ** 0.5 lux minimum must be used for areas larger than 60m², the maximum value is to be measured across the area excluding 0.5 metre border around the edge of the room
- *** Explanation of the symbols:-
Transverse - Wall
 Distance to wall from side of fitting
Transverse - Transverse
 Side to side spacing
Axial - Wall
 Distance to wall from end of fitting
Axial - Axial
 End to end spacing

Code	Lamp	Description
ABLED/3NM	LED	5W Non-Maintained

Accessory	ASBP/9	3.6V 4.5Ah Ni-Cd Replacement Battery
-----------	--------	--------------------------------------

LED Information

Total (Watts)	5W
Lumens Delivered	
Emergency Mode	136lm
Beam Angle	120°
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0°C to 45°C

