



MTN106

MCBs - Single Pole, B Curve, 6kA

Characteristics:

- Protection and control of circuits against overloads and short circuits for use in domestic installations.
- Complies with BS EN 60898.
- Voltage rating: 230V
- Current rating: 6 - 63A
- Connection capacity: Rigid = 25mm², Flexible = 16mm²
- Calibration temperature: 30°C

Description	Width (1 Mod =17.5mm)	Cat ref.
6A	1 Mod	MTN106
10A	1 Mod	MTN110
16A	1 Mod	MTN116
20A	1 Mod	MTN120
25A	1 Mod	MTN125
32A	1 Mod	MTN132
40A	1 Mod	MTN140
50A	1 Mod	MTN150
63A	1 Mod	MTN163



ADA332G

Reduced Height RCBO - Single Pole, B Curve, 6kA, 30mA, Type A

Characteristics

- Protection devices which combine the overcurrent functions of an MCB with the earth fault functions of an RCCB.
- Complies with BS EN 61009-1, BS IEC 1009-2-2
- Single module width
- Sensitivity: 30mA
- Current rating: 6 - 32A
- Connection capacity: Rigid = 16mm², Flexible = 10mm²
- Flying neutral lead: 200mm
- Single pole & solid neutral
- Type A (Pulsating DC Sensitive)
- Operational Voltage: 127-230V AC

Description	Cat ref.
6A	ADA306G
10A	ADA310G
16A	ADA316G
20A	ADA320G
25A	ADA325G
32A	ADA332G