



# Datasheet

## Alfresco Urban

### Product Description

The design for Alfresco Urban is simple and classic and it will suit most wall mounted applications.


### Specification Text

The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 107.0 lm/W and will be capable of producing up to 2,147 luminaire lumens at 4000K with a CRI >80. It shall have an asymmetric forward throw optic and is rated at IP65 and IK08.

### Specification

Weight: 2.4 - 2.8kg  
Material: Die-cast Aluminium  
Paint finish: RAL7016 Anthracite Grey Finish


### Optics



Asymmetrical 180 x 90°

### Key Features

- 20.0W
- 2,147 Luminaire Lumens
- Efficacy up to 107 lm/W
- 4000K, CRI >80
- Lifetime >50,000hr, L70



### Mounting Options

- Wall Mount

### Other Options

- Colour Temperature Options
  - Photocell Option
  - Motion Sensor Option
  - Emergency Option
- [Contact for details](#)

Code	Power	Luminaire Lumens	Drive Current	Optic	CCT(K)	IP	IK	Weight kg	Paint Finish	Driver Included
ALFH20F	20.0	2,147	500	Asymmetrical 180 x 90°	4000	IP65	IK08	2.5	RAL7016 Anthracite Grey	Driver Inc
ALFH20FEM	20.0	2,147	500		4000	IP65	IK08	2.5	RAL7016 Anthracite Grey	Driver Inc
ALFH20FEMPEC	20.0	2,147	500		4000	IP65	IK08	2.5	RAL7016 Anthracite Grey	Driver Inc
ALFH20FPEC	20.0	2,147	500		4000	IP65	IK08	2.5	RAL7016 Anthracite Grey	Driver Inc



## Dimensions

