Xnightsbridge

DATASHEET



AMLEDW

230V IP54 5W LED Security Amenity Bulkhead White

Base with Opal Diffuser Cool White 4000K

www.mlaccessories.co.uk



DIFFUSER Opal Length - 197 Width - 108 Projection - 78 CONSTRUCTION Construction - Polycarbonate CLASS II IP RATING IP54 WATTAGE (W) 5 LAMP TECHNOLOGY SMD LED LAMP INCLUDED Yes LUMENS (LM) 460 LUMENS LIGHT SOURCE ONLY (LM) 520 LUMEN TOLERANCE 5% EFFICACY (LM/W) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	MLA PART CODE	AMLEDW
DIFFUSER Opal Length - 197 Width - 108 Projection - 78 CONSTRUCTION Construction - Polycarbonate CLASS II IPF RATING IP54 WATTAGE (W) 5 LAMP TECHNOLOGY SMD LED LAMP INCLUDED Yes LUMENS (LM) 460 LUMENS LIGHT SOURCE ONLY (LM) 520 LUMEN TOLERANCE 5% EFFICACY (LM/W) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	DESCRIPTION	230V IP54 5W LED Security Amenity Bulkhead White Base with Opal Diffuser Cool White 4000K
Length - 197 Width - 108	FINISH	White
DIMENSIONS (MM) Width - 108 Projection - 78 CONSTRUCTION Construction - Polycarbonate CLASS II IP RATING IP54 WATTAGE (W) 5 LAMP TECHNOLOGY SMD LED LAMP INCLUDED Yes LUMENS (LM) 460 LUMENS LIGHT SOURCE ONLY (LM) 520 LUMEN TOLERANCE 5% EFFICACY (LMW) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6	DIFFUSER	Opal
II IP RATING	DIMENSIONS (MM)	Width - 108
IP RATING	CONSTRUCTION	Construction - Polycarbonate
WATTAGE (W) 5 LAMP TECHNOLOGY SMD LED LAMP INCLUDED Yes LUMENS (LM) 460 LUMENS LIGHT SOURCE ONLY (LM) 520 LUMEN TOLERANCE 5% EFFICACY (LM/W) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	CLASS	II
LAMP TECHNOLOGY SMD LED LAMP INCLUDED Yes LUMENS (LM) 460 LUMENS LIGHT SOURCE ONLY (LM) 520 LUMEN TOLERANCE 5% EFFICACY (LM/W) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	IP RATING	IP54
LAMP INCLUDED Yes LUMENS (LM) 460 LUMENS LIGHT SOURCE ONLY (LM) 520 LUMEN TOLERANCE 5% EFFICACY (LM/W) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	WATTAGE (W)	5
LUMENS (LM) 460 LUMENS LIGHT SOURCE ONLY (LM) 520 LUMEN TOLERANCE 5% EFFICACY (LM/W) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	LAMP TECHNOLOGY	SMD LED
LUMENS LIGHT SOURCE ONLY (LM) 520 LUMEN TOLERANCE 5% EFFICACY (LM/W) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	LAMP INCLUDED	Yes
LUMEN TOLERANCE 5% EFFICACY (LM/W) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	LUMENS (LM)	460
EFFICACY (LM/W) 100 CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	LUMENS LIGHT SOURCE ONLY (LM)	520
CIRCUIT WATTAGE (W) 5.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	LUMEN TOLERANCE	5%
CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6	EFFICACY (LM/W)	100
LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	CIRCUIT WATTAGE (W)	5.3
CRI >80 SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	ССТ	4000K
SDCM <6 RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	LIGHT COLOUR	Cool White
RUNNING CURRENT (A) 0.023 DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	CRI	>80
DISPLACEMENT FACTOR >0.9 SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	SDCM	<6
SVM 0.001 PST-LM 0.185 BEAM ANGLE (DEGREES) 120	RUNNING CURRENT (A)	0.023
PST-LM 0.185 BEAM ANGLE (DEGREES) 120	DISPLACEMENT FACTOR	>0.9
BEAM ANGLE (DEGREES) 120	SVM	0.001
	PST-LM	0.185
LIFE SPAN (HRS) 30,000	BEAM ANGLE (DEGREES)	120
	LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS) 60,000	L70B50 LIFESPAN (HRS)	60,000





Xnightsbridge

DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	110/230V
CABLE ENTRY (MM)	20
DRIVER	MAX. OUTPUT - 5W OUTPUT VOLTAGE - 29-35V OUTPUT CURRENT - 150mA POWER FACTOR - 0.46 EFFICIENCY FULL LOAD - 85 CASE TEMPERATURE (Tc) - 80°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832931850

Date Created: 08/01/2024 12:54





