

AFT/MBS, Rohranschluss mit Innengewinde;
 hellgrau (RAL 7035), grau (RAL 7037), schwarz (RAL 9005)
 oder weiß (RAL 9010), zum Anschluss von starren oder
 biegsamen Rohren an Abzweig- und Panzerkästen



**AFT/MBS, adaptor with female thread and male
 bush;** light grey (RAL 7035), grey (RAL 7037), black (RAL 9005) or
 white (RAL 9010), for the connection of rigid or pliable conduits with
 distribution and enclosure boxes

Material				Temp.			
PVC-U				-5°C/+60°C *(-25°C/+60°C)			
art	dn	ps	pl	ref			
				hellgrau light grey	grau* grey*	schwarz black	weiß white
AFT/MBS 16	16,0	100	2400	020 754	020 783	009 085	010 183
AFT/MBS 20	20,0	100	1200	020 755	020 784	009 086	010 184
AFT/MBS 25	25,0	50	600	020 756	020 785	009 087	010 185
AFT/MBS 32	32,0	20	480	020 757	020 786	009 088	010 186
AFT/MBS 40	40,0	25	300	020 758	020 787	009 089	010 187
AFT/MBS 50	50,0	10	120	020 759	020 788	009 090	010 188

AMT/LR, Rohranschluss mit Gewinding;
 hellgrau (RAL 7035), grau (RAL 7037), schwarz (RAL 9005)
 oder weiß (RAL 9010), zum Anschluss von starren oder
 biegsamen Rohren an Abzweig- und Panzerkästen



AMT/LR, adaptor with male thread and lock ring;
 light grey (RAL 7035), grey (RAL 7037), black (RAL 9005) or
 white (RAL 9010), for the connection of rigid or pliable conduits with
 distribution and enclosure boxes

Material				Temp.			
PVC-U				-5°C/+60°C *(-25°C/+60°C)			
art	dn	ps	pl	ref			
				hellgrau light grey	grau* grey*	schwarz black	weiß white
AMT/LR 20	20,0	100	1200	009 574	020 790	009 548	009 600
AMT/LR 25	25,0	50	600	009 575	020 791	009 549	009 601

MBS, Gewindestück; schwarz (RAL 9005) oder
 weiß (RAL 9010)



MBS, male bush; black (RAL 9005) or white (RAL 9010)

Material				Temp.			
PVC-U				-5°C/+60°C			
art	dn	ps	pl	ref			
				schwarz black	weiß white		
MBS 16	16,0	100	2400	009 079	010 189		
MBS 20	20,0	100	1200	009 080	010 190		
MBS 25	25,0	50	600	009 081	010 191		
MBS 32	32,0	20	480	009 082	010 192		
MBS 40	40,0	25	300	009 083	010 193		
MBS 50	50,0	10	120	009 084	010 194		