












Tornado EVO


Tornado EVO CCT Multi Wattage 1500mm Code: ATORE5/1/MWS





| Specification | Performance |
|---|---------------------------------|
| | Hospitality, Industrial, Retail |
| Application Ancillary, Commercial, Education, Healtho | |
| Category | Baffens and Weatherproofs |





PRODUCT FEATURES

- $_{\bullet}\,$ IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire
- LED performance allows point-to-point replacement of existing fluorescent luminaires
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation
- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

| GENERAL INFORMATION | | |
|-------------------------|-------------------------|--|
| Wattage | 30W/60W | |
| Lumens Delivered | 4700lm - 9300lm (4000K) | |
| Lm/W | 160lm/W (4000K) | |
| Beam Angle | 120 | |
| CRI | 80 | |
| CCT | 4000/5000/6500K | |
| Input | 220/240V | |
| Operating Temp | -20°C - 40°C | |
| SDCM | 6 | |
| Energy efficiency class | D | |

| TECHNICAL INFORMATION | | | |
|--------------------------------|---------------------|--|--|
| Light Source | LED | | |
| Colour / Finish | Grey | | |
| IP Rating | IP65 | | |
| Class Protection | 1 | | |
| Internal / External | Internal / External | | |
| Surface / Recessed / Suspended | Ceiling, Suspended | | |
| Lumen Depreciation | L80 72,000h | | |
| Warranty (Years) | 5 | | |
| CE Mark | Yes | | |
| Height | 80 mm | | |

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750