



DATASHEET



BATSCWM6

230V 6ft 27/52W CCT Adjustable Microwave Batten

www.mlaccessories.co.uk



MLA PART CODE	BATSCWM6
DESCRIPTION	230V 6ft 27/52W CCT Adjustable Microwave Batten
NET WEIGHT (KG)	1.85
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1790 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	27/52
LAMP TECHNOLOGY	LED
LUMENS (LM)	3750/4170/4070, 6590/7520/7150
LUMENS LIGHT SOURCE ONLY (LM)	8410
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	165.5
CIRCUIT WATTAGE (W)	50.82
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.223
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	145
L70B50 LIFESPAN (HRS)	60,000
DIMMABLE	No

OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 26/52W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 600/1200mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 97.1 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
SENSOR TYPE	Microwave
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	150 (wall mounted) / 360 (ceiling mounted)
OPTIMUM DETECTION RANGE (M)	6m at height 3m, max. mounting height 6m
SENSOR DURATION	5 seconds - 30 minutes
SENSOR LUX SETTINGS	2 lux - 50 lux / Disable
STANDBY POWER	≤ 0.5WW
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270881622

Date Created: 08/01/2024 20:42

