Pre-Insulated Crimp Terminals: Product Overview

- A complete range of pre-insulated terminals that combine high quality with competitive pricing.
- High grade PVC insulation makes crimping easy whilst ensuring complete integrity of termination.
- VR indicates 'Vibration Resistant' Extra copper ring within the crimp terminal.
- Available in packs of 100 or 1000 pieces as standard.

Metric (mm)

- Red Insulation: Conductor size 0.5-1.5mm² / 22-16awg.
- Blue Insulation: Conductor size 1.5-2.5mm² / 16-14awg.
- Yellow Insulation: Conductor size 4.0-6.0mm²/ 12-10awg.
- UL approval number: E163810

Imperial

(conversions continued)		
Imperial	Metric (mm)	
1/2"	12	
9/16"	14	
5/8"	16	
11/16"	18	
3/4"	20	
7/8"	22	
1"	25	

8BA 2 3 6BA 4BA 3.5 3BA 4 2BA 5 0BA 6 5/16" 8 3/8" 10

Terminals - Imperial/Metric Conversion

Pre-Insulated Crimp Terminals: Rings



Ring Terminals		
Part No.	Stud Size (mm)	Insulation Colour
RR32	3	Red
RR37	3.5	Red
RR43	4	Red
RR53	5	Red
RR64	6	Red
RR84	8	Red
RR105	10	Red
BR32	3	Blue
BR37	3.5	Blue
BR43	4	Blue
BR53	5	Blue
BR64	6	Blue
BR84	8	Blue
BR105	10	Blue
BR120	12	Blue
YR43	4	Yellow
YR53	5	Yellow
YR64	6	Yellow
YR84	8	Yellow
YR105	10	Yellow
YR120	12	Yellow