

Optional stainless steel frame included



**LED LAMP SPECIFICATIONS:**


Luminaire lumens (with diffuser)	<b>285 lm</b>
Lumens from chip (no diffuser)	<b>700 lm</b>
Useful lumens	<b>265 lm</b>
Rated Wattage	4.5W
Rated luminous flux	265 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	6000K
Number of switching cycles before premature lamp failure	15,000
Warm-up time up to 60% of the full light output	<2s
Dimmable	No
Nominal beam angle	120°
Rated power	4.5W
Rated lamp lifetime	30,000 hrs
Displacement factor	≥0.9
Lumen maintenance factor at end of nominal life	≥0.7
Starting time	<0.5s
Colour rendering	≥80
Colour consistency	Within a six step Macadam ellipse
Rated peak intensity	84cd
Rated beam angle	120°
Voltage / Frequency	240V~50Hz

**LED BRICKLIGHT WITH STAINLESS STEEL FRAME**

A modern design that gives an instant cool white light. Ultra low energy consumption and prolonged lamp life.

- Polycarbonate construction
- Opal diffuser with optional stainless steel frame offering a soft, stylish lighting effect
- Integral driver
- Cable gland included
- 5 year warranty

• M.O.M: 1 / O.P.Q: 6



Code	Colour	Wattage	Colour Temp.	Luminaire Lumens	Avg. Rated Life (Hrs)	IP Rating
BRICKLED	White / Stainless Steel	4.5W	6000K	285 lm	30,000 hrs	IP65

Cable gland included

Lumen efficacy: 63 lm / W

This product contains a Light Source of Energy Efficiency Class E

Not suitable for accent lighting