

Product Code: CL019

Description: 10AX 4 Gang 2 Way Plate Switch



### General Information

<b>Dimensions</b>	140mm (W) x 80mm (H) x 42mm (D)
<b>Finish</b>	Metal Clad Grey
<b>Insert Colour</b>	White (WH)
<b>Materials</b>	Front Plate & Pattress Box: Electrophoretically Coated Steel Insert & Rocker Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
<b>Maximum Voltage</b>	250V~ 50Hz
<b>Load Rating</b>	10AX (Suitable for Inductive Loads)
<b>Plate Fixing Centres</b>	120.6mm
<b>Terminal Size</b>	3.5mm $\varnothing$
<b>Terminal Torque</b>	0.5Nm
<b>Terminal Capacity</b>	4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>
<b>Two Way</b>	Yes
<b>Back Box Depth</b>	40mm Supplied
<b>Termination Type</b>	Screw
<b>Earth Terminal Provided</b>	Yes
<b>Back Box Knockouts</b>	7 x 20mm (3 on top, 2 on bottom, 1 on each side)
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years
<b>Standards</b>	BS EN 60669-1:1999 +A1:2002 +A2:2008

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)