



Product Code: CL032

Luckinslive 436090943

Description: 13A 2 Gang Unswitched Socket Outlet



General Information

Dimensions (mm)	140 (W) x 80 (H) x 42 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Metal Clad	
Colour	Grey	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert & Rocker Switch: Urea
	Rear Housing: Urea	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Switched	No	
Twin Earth Terminals	Yes	
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	7 x Ø20	Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Knockouts - Top (mm)	3 x Ø20	Back Box Knockouts - Rear (mm) None
Back Box Knockouts - Bottom (mm)	2 x Ø20	
Back Box Earth Terminal Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

