

**Product Code:** CL675

**Description:** 13A 1 Gang Double Pole Key Lockable Switched Socket With Neon (Double Plate)



Representative Image

### General Information

<b>Dimensions</b>	140mm (W) x 80mm (H) x 42mm (D)
<b>Finish</b>	Metal Clad Grey
<b>Materials</b>	Front Plate & Pattress Box: Electrophoretically Coated Steel Insert: Urea Earth Plate & Yoke: Mild Steel Neon Lens: Polycarbonate Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass GridPro Module: GM2008PW
<b>Maximum Voltage</b>	250V~ 50Hz
<b>Load Rating</b>	13A
<b>Plate Fixing Centres</b>	120.6mm
<b>Terminal Size</b>	5mmø
<b>Terminal Torque</b>	1.2Nm
<b>Terminal Capacity</b>	3 x 2.5mm <sup>2</sup> , 2 x 4mm <sup>2</sup>
<b>Double Pole</b>	Yes
<b>Twin Earth Terminals</b>	Yes
<b>Neon Indicator</b>	Yes (Red)
<b>Product Markings</b>	On / Off
<b>Back Box Depth</b>	40mm Supplied
<b>Earth Terminal Provided</b>	Yes
<b>Back Box Knockouts</b>	7 x 20mm (3 on top, 2 on bottom, 1 on each side)
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years
<b>Standards</b>	BS EN 60669-1:1999 +A1:2002 +A2:2008 BS 1363-2: 2016 +A1: 2018

### Additional Information

Two keys provided (Spare keys available: SP660)  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.