



CL035



CL036



CL771U



CL780



CL835



CL840

Switched Socket Outlets

- CL035** 13A 1 Gang DP Switched Socket
- CL035B** 13A 1 Gang DP Switched Socket (No Knockouts)
- CL036** 13A 2 Gang DP Switched Socket
- CL036B** 13A 2 Gang DP Switched Socket (No Knockouts)

Switched Socket Outlets

- CL835** 13A 1 Gang Switched Socket With Outboard Neon Rocker
- CL840** 13A 2 Gang Switched Socket With Outboard Neon Rockers

Switched Sockets With USB Outlets

- CL771U** 13A 1 Gang Switched Socket With 2.1A USB Outlet (Twin Earth)
- CL770** 13A 2 Gang Switched Socket With 2.1A USB Outlet (Twin Earth)
- CL780** 13A 2 Gang Switched Socket With Twin 2.1A USB Outlets (4.2A) (Twin Earth)

Standards: BS1363 770, 771; BS5733, BS60950-1, EN61000-6-1, EN 61000-6-3 Back Box Depth: 40mm Minimum
 Cable Size: 4 x 2.5mm² / 2 x 4mm² Knock-outs: 20mm
 Dimensions: 1 Gang: (80mm x 80mm), 2 Gang: (140mm x 80mm)



CL1035



CL1036



CL1835



CL1840

Safety Shutter Sockets

- CL1035** 13A 1 Gang DP 3 Pin Safety Shutter Switched Socket
- CL1035B** 13A 1 Gang DP 3 Pin Safety Shutter Switched Socket (No Knockouts)
- CL1835** 13A 1 Gang DP 3 Pin Safety Shutter Switched Socket With Neon
- CL1835B** 13A 1 Gang DP 3 Pin Safety Shutter Switched Socket With Neon (No Knockouts)
- CL1036** 13A 2 Gang DP 3 Pin Safety Shutter Switched Socket (Twin Earth)
- CL1036B** 13A 2 Gang DP 3 Pin Safety Shutter Clean Earth Switched Socket (Twin Earth) (No Knockouts)
- CL1840** 13A 2 Gang DP 3 Pin Safety Shutter Switched Socket With Outboard Rockers & Neons (Twin Earth)
- CL1840B** 13A 2 Gang DP 3 Pin Safety Shutter Switched Socket With Outboard Rockers & Neons (Twin Earth) (No Knockouts)

Standards: BS1363; 675; BS1363-2, BS EN 60669-1 Back Box Depth: 40mm Minimum
 Cable Size: 4 x 2.5mm² / 2 x 4mm² Knock-outs: 20mm
 Dimensions: 1 Gang: (80mm x 80mm), 2 Gang: (140mm x 80mm)