



CMA215



PRW217



CMA060



CMA100

Click® dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5: 2010 making it safe for use in bathrooms. Shaver outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet

**Flex Outlet Plates**

**CMA017** 20A Flex Outlet Plate

**45A Cooker Connection Plates**

**CMA215** 45A 1 Gang Cooker Connection Plate

**45A Cooker Outlet Plates**

**PRW217** 45A Easyfit Dual Appliance Outlet Plate

**Pattress Box for PRW217 - Urea**

**PRW218** 35mm Deep Pattress Box For Use With PRW217

**Dual Voltage Shaver Socket**

**CMA100** 115/230V Dual Voltage Shaver Socket

**Blank Plates**

**CMA060** 1 Gang Blank Plate

**CMA061** 2 Gang Blank Plate

Standards: 100: BS EN 61558 017/215/217: BS 5733  
 Back Box Depth: 017: 16mm min 100: 47mm min 215: 35mm min 217: 25mm min  
 Cable Size: 215: 2 x 10mm<sup>2</sup> 100: 2 x 1.5mm<sup>2</sup> / 1 x 2.5mm<sup>2</sup> 017: 1 x 6mm<sup>2</sup> / 4 x 2.5mm<sup>2</sup> 217: 1 x 10mm<sup>2</sup>  
 Dimensions: 215: 86mm x 86mm x 22.5mm 217: 84mm x 130mm x 27mm

# TV, Telephone & Data Sockets

Providing the means to facilitate the connection of modern communications equipment is as important today as it is to provide the electrical power to operate them.

This section of the catalogue is devoted to the New Media™ range of plate accessories which includes products for connecting telephone, computer, television and satellite devices.



RJ11 Outlet | UK Telephone Outlets  
 Satellite Socket Outlets | Coaxial Sockets

