




CMA115 / CMA131



CMA132



CMA122 / CMA127



CMA119 / CMA124



CMA065



CMA066



CMA156




CMA170



CMA157



CMA158



CMA159

RJ11 Telephone Outlet

CMA115 Single RJ11 (Irish/US) Outlet

RJ45 Data Outlets

CMA131 Single RJ45 Cat-5e Outlet

CMA132 Twin RJ45 Cat-5e Outlet

Telephone Outlets

CMA119 Single Telephone Outlet - Master

CMA122 Twin Telephone Outlet - Master

CMA124 Single Telephone Outlet - Secondary

CMA127 Twin Telephone Outlet - Secondary

Twin outlets are 2 separate sockets and not internally linked together.

Back Box Depth: 25mm Minimum 115: 35mm Minimum Termination Type: IDC
Dimensions: 1 Gang: (86mm x 86mm x 9.5mm)

Non-Isolated Coaxial Outlets (Unshielded)

CMA065 Single Coaxial Outlet

CMA066 Twin Coaxial Outlet

Isolated Coaxial Outlets (Unshielded)

CMA158 Single Coaxial Outlet

CMA159 Twin Isolated Coaxial Outlet

Satellite Outlets (Unshielded)

CMA157 Isolated Satellite & Isolated Coaxial Outlet

CMA170 Non-Isolated Satellite & Non-Isolated Coaxial Outlet

CMA156 Non-Isolated Single Satellite Outlet

Isolated outlets will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Back Box Depth: 16mm Minimum
Dimensions: 1 Gang: (86mm x 86mm x 9.5mm)