

Product Code: CMA145PL

Description: 1 Gang Unfurnished Dimmer Plate & Knob (650W Max) - 1 Aperture



General Information

Dimensions	86mm (W) x 86mm (H) x 9.5mm (D)
Material Composition	Front Plate & Control Button: Urea
Fixing Centres	60.3mm
Terminal Size	Dependent On Modules Fitted
Terminal Torque	Dependent On Modules Fitted
Terminal Capacity	Dependent On Modules Fitted
Control Type	Dependant On Module Installed
Back Box Depth	Dependent On Modules Fitted
Temperature Rating	-5°C to +40°C
Warranty	20 Years

Standards BS 5733: 2010 +A1: 2014

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.
 All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.
 Interchangeable with dimmer modules in the MiniGrid Range.
 Suitable for dimmer modules with M10 thread and maximum width 50mm.

Interchangeable Modules

MD9014: 100W Dual Mode LED Dimmer Module
 MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module
 MD9010: 1-10V Analogue Rotary Dimmer Module
 MD9022: 40-250W Leading Edge Dimmer Module
 MD9042: 60-400W Leading Edge Dimmer Module