

Product Code: CMA603

Technical Specification









General Information

Plate Dimensions (mm) 250 (W) x 86 (H) x 8 (D)

New Media Aperture Dimensions (mm) 75 x 50

> New Media Module Quantity Accepts Upto 3 x 25mm x 50mm Modules

> > Style Mode Colour Polar White

Materials Front Plate & Rear Housing: Urea Terminals: Brass

> Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Anti Microbial Certified Yes

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) Termination Type Screw

> Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes Twin Earth Terminals Compatible Back Box (mm) MP520 (47) Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years) 25

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Requires MP520 flush back box.

Interchangeable with modules in the New Media Range.











Specification is subject to change without notice. Errors & Omissions excluded.