

Cat No.	Description	Rating	Modules	Inner Carton
RCD Type AC				
CUR4030	Double Pole, Type AC	40A 30mA	2	5
CUR6330	Double Pole, Type AC	63A 30mA	2	5
CUR8030	Double Pole, Type AC	80A 30mA	2	5
CUR80100	Double Pole, Type AC	80A 100mA	2	5
CUR80100TD	Double Pole, Type AC, Time Delayed	80A 100mA	2	5
RCD Type A				
CUR4030A	Double Pole, Type A RCD	40A 30mA	2	5
CUR6330A	Double Pole, Type A RCD	63A 30mA	2	5
CUR8030A	Double Pole, Type A RCD	80A 30mA	2	5
CUR10030A	Double Pole, Type A RCD	80A 100mA	2	5



- Positive contact status indication
- Device capable of being locked in 'ON' or 'OFF' position using a device lock

Cat No.	Description	Modules	Inner Carton
Control Devices			
CUC20	Contacteur 20A double pole	1	5
CUC40	Contacteur 40A double pole	2	5
CUB1	Bell Transformer	2	5
CUTS1	Time Delay Switch, 1 - 20 mins	1	5
CUTS5	Timer Analogue 24 Hr	3	5
CUTS10	Timer Digital 1 Channel	2	5
CUTS11	Timer Digital 2 Channels	2	5

- Wide range of additional control devices for installation inside the consumer unit
- Contactors are Ideal for controlling large lighting loads, heating or ventilation systems
- The bell transformer is for use with mains powered door chimes which do not have integrated transformers
- Step down transformer to 8V-24V
- The timers control circuits to activate or deactivate at certain times the user sets
- The number of channels indicates the number of separate circuits which can be controlled

