

## Residential downlights



**Patented Easy-fit  
connector for first &  
second fix**




**Shallow depth 46mm**



**Insulation coverable**

<b>Guarantee</b>	10 years
<b>Connector</b>	Easy-fit connector
<b>IP rating</b>	IP65 (from below) IP20 (from above)
<b>Bathroom zone</b>	1
<b>Dimmable</b>	Yes (TRIAC mains dimmable)
<b>Tiltable</b>	No
<b>CRI</b>	80 Ra
<b>Input</b>	220-240V 50/60Hz
<b>SELV</b>	Yes
<b>Building regulations</b>	Part B, C, E, P & L
<b>Cut-out size</b>	Ø 64-72mm
<b>Insulation coverable</b>	Rolled and blown insulation
<b>Ceiling joist approved</b>	Solid timber, I-Joist and Metal Web



# H2 Lite fixed

TRIAC Dimmable, fire-rated downlight with integrated bezel & Easy-fit connector

**10** year  
guarantee



Product code	Finish	Wattage	Colour	Beam	lm	lm/W	lx at 1m
DLT388BLK5530	Matt black	4.3W	3000K	55°	460	107	413
DLT388BLK5540	Matt black	4.3W	4000K	55°	490	114	440
DLT388BS5530	Brushed steel	4.3W	3000K	55°	460	107	413
DLT388BS5540	Brushed steel	4.3W	4000K	55°	490	114	440
DLT388MW5530	Matt white	4.3W	3000K	55°	460	107	413
DLT388MW5540	Matt white	4.3W	4000K	55°	490	114	440