

Residential downlights



Colour switchable
between 2700K, 3000K
and 4000K




Wattage switchable
between 4.2W & 6W



High efficacy of
124lm/W

Guarantee	7 years
Connector	2 part first fit connector
IP rating	IP65 (from below) IP20 (from above)
Bathroom zone	1
Dimmable	Yes (TRIAC mains dimmable)
Tiltable	No
CRI	80 Ra
Input	220-240V 50/60Hz
SELV	Yes
Building regulations	Part B, C, E, P & L
Cut-out size	Ø 68-72mm
Insulation coverable	Rolled and blown insulation
Ceiling joist approved	Solid timber, I-Joist and Metal Web



H2 Lite CSP fixed

Colour & Wattage Switchable using switches under bezel



All in 1

stock less &
sell more

**Click Flow
compatible**



Multipack
8 x H2 Lite CSP
White bezel included



Product code	Finish	Type	Wattage	Colour	Beam	lm	lm/W	lx at 1m
DLT551500A	Bezel sold separately See page 21	Single unit	4.2W	2700K	55°	450	107	409
				3000K	55°	520	124	472
				4000K	55°	500	119	454
			6W	2700K	55°	625	104	567
				3000K	55°	720	120	654
				4000K	55°	700	117	636
DLT551500A8	White	Multipack	4.2W	2700K	55°	450	107	409
				3000K	55°	520	124	472
				4000K	55°	500	119	454
			6W	2700K	55°	625	104	567
				3000K	55°	720	120	654
				4000K	55°	700	117	636