

# Ei450

## RadioLINK Alarm Controller



- Install as part of the system to get more control over your alarms
- Test, Locate and Silence functions
- RadioLINK+ Wireless interconnection
- 10 year Lithium battery powered
- LEDs for a visual display of Fire or Carbon Monoxide alarm activation



### Description

The Ei450 RadioLINK Alarm Controller is used to control all wirelessly interconnected fire and CO alarms from one location. It allows the user to remotely Test, Locate and Silence alarms in the system and is powered by a built-in 10 year lithium cell

### Technical

<b>RF Frequency (MHz)</b>	868.499	<b>RF Range (m)</b>	>100 in free air
<b>Indicators</b>	Red - Fire, CO / Yellow - EoL	<b>Battery Type</b>	Lithium primary
<b>Technologies</b>	RadioLINK		

### Dimensions & Weights

<b>Depth (mm)</b>	27	<b>Height (mm)</b>	90
<b>Width (mm)</b>	90	<b>Product weight (kg)</b>	0.112
<b>Packaged weight (kg)</b>	0.178		

### Approvals & Warranty

<b>Certification/Approvals</b>	EN 300-220-2 / EN 301 489-1, EN 301 489-3 / EN 60065	<b>Warranty</b>	5 year warranty
<b>EAN Number</b>	5099383004731		

### Environmental

<b>Humidity Range (%)</b>	15-95	<b>Temperature Range (°C)</b>	-10 to 40
---------------------------	-------	-------------------------------	-----------