

- 5500K colour temperature
- Viewing distance - 25m
- SMD 2835 LED Lamp
- Steel housing
- Wall mounted
- Charge and discharge protection
- Green LED Indicator
- 3 Hours Emergency Duration
- 3.6V 1500mAH NI-CAD Battery
- BS EN 60598-2-22 Standards
- Dimensions - 390 x 190 x 60mm
- Weight - 1.3Kg



**EMBAT3.6V1500**  
3.6V 1500mAH Battery

**EMLED3WMEXBOXBR**

3W LED Maintained Emergency Brass Sign



**EMLED3WMEXBOXBRU**  
3W LED Maintained  
Emergency Brass Sign UP



**EMLED3WMEXBOXBRD**  
3W LED Maintained  
Emergency Brass Sign DOWN



**EMLED3WMEXBOXBRL**  
3W LED Maintained  
Emergency Brass Sign LEFT



**EMLED3WMEXBOXBRR**  
3W LED Maintained  
Emergency Brass Sign RIGHT

- 5500K colour temperature
- Viewing distance - 25m
- SMD 2835 LED Lamp
- Steel housing
- Wall mounted
- Charge and discharge protection
- Green LED Indicator
- 3 Hours Emergency Duration
- 3.6V 1500mAH NI-CAD Battery
- BS EN 60598-2-22 Standards
- Dimensions - 390 x 190 x 60mm
- Weight - 1.3Kg



**EMBAT3.6V1500**  
3.6V 1500mAH Battery

**EMLED3WMEXBOXBK**

3W LED Maintained Emergency Black Sign



**EMLED3WMEXBOXBKU**  
3W LED Maintained Emergency  
Black Sign UP



**EMLED3WMEXBOXBKD**  
3W LED Maintained Emergency  
Black Sign DOWN



**EMLED3WMEXBOXBKL**  
3W LED Maintained Emergency  
Black Sign LEFT



**EMLED3WMEXBOXBKR**  
3W LED Maintained Emergency  
Black Sign RIGHT