

## DATASHEET



### EMPOWER4WST

**230V IP20 3.5W LED Self-test Emergency Downlight 3000K (maintained/non-maintained use)**

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)

MLA PART CODE	EMPOWER4WST
DESCRIPTION	230V IP20 3.5W LED Self-test Emergency Downlight 3000K (maintained/non-maintained use)
NET WEIGHT (KG)	0.22
FINISH	White
DIMENSIONS (MM)	Diameter - 60 Length - 183 Recessed Depth - 32 Minimum Void - 80
CUT-OUT (MM)	Cut-out Diameter - 45
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	3.5
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	130
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	35.9
LUMENS EMERGENCY MODE (LM)	130
CIRCUIT WATTAGE (W)	3.6
CCT	3000K
LIGHT COLOUR	Warm White
CRI	>70
RUNNING CURRENT (A)	0.028
BEAM ANGLE (DEGREES)	140
L70B50 LIFESPAN (HRS)	30000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Yes

IC RATED	No
OPERATING TEMPERATURE	0~25°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.35
CABLE TYPE	H05VV-F
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598-1, BS EN 60598-2-22
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270876260

Date Created: 08/01/2024 20:34

