

20 Amp Double Pole Switches

- 20 Amp
- Terminal capacity 3 x 2.5mm² 2 x 4.0mm² 1 x 6.0mm²
- Colour coded terminals with backed out angled screws
- Flush LED power indicator
- Manufactured to BS EN 60669-1
- Minimum mounting box depth 25mm



Brushed Steel	Polished Chrome	Black Nickel	Description	Inner Carton	Outer Carton
FBS31	FPC31	FBN31	20A double pole with power indicator	5	50

45 Amp Double Pole Switches

- Cooker Control Units manufactured to BS4177, Double Pole Switches to BS EN 60669-1
 - L & N terminal capacity 4 x 4.0mm², 3 x 6.0mm² & 1 x 16.0mm²
 - Minimum mounting box depth 47mm
- *Insert colours = White (W), Grey (G) and Black (B) at the end of the product code



Brushed Steel	Polished Chrome	Black Nickel	Description	Inner Carton	Outer Carton
FBS70G	FPC70G	FBN70B	With 13 Amp socket and power indicator	5	50
-	FPC70W	-	-	5	50
FBS72	FPC72	FBN72	Double plate, with power indicator	5	50
FBS74	FPC74	FBN74	Single plate, with power indicator	5	50

Round Pin and Export Socket Outlets

- 2/5/15A Manufactured to BS 546
 - Mounting box depth:
13A and 15A: 35mm, 2A, 5A and 16A: 25mm
- *Insert colours = White (W), Grey (G) and Black (B) at the end of the product code



Brushed Steel	Polished Chrome	Black Nickel	Description	Inner Carton	Outer Carton
FBS28G	FPC28G	FBN28B	2 Amp unswitched socket round pin	5	50
-	FPC28W	-	-	-	-
FBS29G	FPC29G	FBN29B	5 Amp unswitched socket round pin	5	50
-	FPC29W	-	-	-	-
FBS29SG	FPC29SW	FBN29SB	Single, 5 Amp, switched socket, round pin (Export only)	5	50
FBS27G	FPC27G	-	Single, 13 Amp, universal with power indicator	5	50
-	-	-	-	-	-
FBS99G	FPC99G	FBN99B	Single, 15 Amp switched socket	5	50
-	FPC99W	-	-	-	-
FBS98G	FPC98G	-	Double, 16 Amp unswitched Euro socket	5	50
-	FPC98W	-	-	-	-

Fan Controller


- Manufactured to BS EN 60669-2-1
- Minimum mounting box depth 35mm
- 4 speed
- Rotary control



Brushed Steel	Polished Chrome	Black Nickel	Description	Inner Carton	Outer Carton
FBS87	FPC87	FBN87	Single, 1 rotary, 100W (export only)	5	50

13 Amp Fused Connection Units

- Manufactured to BS 1363 Part 4
- Angled colour coded terminals with captive screws
- Minimum mounting box depth 35mm
- Terminal capacity 3 x 2.5mm², 2 x 4.0mm² & 1 x 6.0mm²
- Supplied with pre-fitted 13 Amp fuse



Brushed Steel	Polished Chrome	Black Nickel	Description	Inner Carton	Outer Carton
FBS50	FPC50	FBN50	13 Amp switched	5	50
FBS52	FPC52	FBN52	13 Amp switched with power indicator	5	50
FBS53	FPC53	FBN53	13 Amp switched with power indicator and cable outlet	5	50
FBS54	FPC54	FBN54	13 Amp unswitched	5	50
FBS55	FPC55	FBN55	13 Amp unswitched with power indicator and cable outlet	5	50

Co-Axial and Satellite Sockets

- EM = Euro Module configuration *Supplied as kit of Euro Module components
- TV/FM mounting box depth 25mm, Triplex 35mm
- Insert colours - Polished Chrome = White, Brushed Steel = Grey



Brushed Steel	Polished Chrome	Black Nickel	Description	Inner Carton	Outer Carton
FBS60	FPC60	FBN60	Co-Axial socket, single	5	50
FBS61*	FPC61*	FBN61*	Co-Axial socket, double	5	50
FBS62*	FPC62*	FBN62*	Isolated co-axial socket, single	EM	-
FBS63*	FPC63*	FBN63*	Isolated co-axial socket, double	EM	-
FBS64*	FPC64*	FBN64*	Satellite socket, single	EM	-
FBS65*	FPC65*	FBN65*	Isolated co-axial socket, double	5	50
FBS66*	FPC66*	FBN66*	Diplex TV/FM socket, double	5	50
FBS67*	FPC67*	FBN67*	Triplex TV/FM/Satellite - screened	5	50
FBS68*	FPC68*	FBN68*	Triplex TV/FM/Satellite + return and single, Tel - screened	5	50
FBS69*	FPC69*	FBN69*	Quadplex TV/FM/Satellite (X2) + return and single, Tel - screened	5	50

- See our Euro Module range for further Telecom, Data and Co-axial options