

Residential floodlights

FL01

10W colour switchable floodlight



Guarantee / Warranty: 5 year extended warranty, 3 year on PIR.



PHOTOMETRICS @ 25°C

Product Code	Finish	Sensor	Wattage	Colour	Beam Angle	lm	lm/W	lx at 1m
FL01BXCS	Black	Non PIR sensor	10W	6500K	120°	1300	130	463
				4000K	120°	1150	115	484
				3000K	120°	1100	110	421
FL01BPCS	Black	PIR sensor	10W	6500K	120°	1300	130	463
				4000K	120°	1150	115	484
				3000K	120°	1100	110	421


INSTALLATION INFORMATION

Input	220-240V 50/60Hz
Dimmable	No
Inrush current	10A 262µs
Construction material	Black painted cast aluminium
Weight	Non PIR: 440g PIR: 480g
Class	Class I
Max. ambient temperature	-40°C to 40°C
Flicker free	Yes

BENEFITS

- Colour switchable between 3 colour temperatures
- First mount, detachable circular bracket for speed of install
- A unique 360° rotation for total flexibility, and a 180° tilt
- Suitable for coastal areas
- Performs in even more extreme conditions from -40°C to +40°C
- Supplied with 1m cable
- Wide 120° beam angle, reducing the number of fittings per area required

SIZE DIAGRAM



ACCESSORIES N/A

FL02

20W colour switchable floodlight



Guarantee / Warranty: 5 year extended warranty, 3 year on PIR.



PHOTOMETRICS @ 25°C

Product Code	Finish	Sensor	Wattage	Colour	Beam Angle	lm	lm/W	lx at 1m
FL02BXCS	Black	Non PIR sensor	20W	6500K	120°	2400	120	943
				4000K	120°	2400	120	986
				3000K	120°	2200	110	858
FL02BPCS	Black	PIR sensor	20W	6500K	120°	2400	120	943
				4000K	120°	2400	120	986
				3000K	120°	2200	110	858


INSTALLATION INFORMATION

Input	220-240V 50/60Hz
Dimmable	No
Inrush current	11A 474µs
Construction material	Black painted cast aluminium
Weight	Non PIR: 580g PIR: 620g
Class	Class I
Max. ambient temperature	-40°C to 40°C
Flicker free	Yes

BENEFITS

- Colour switchable between 3 colour temperatures
- First mount, detachable circular bracket for speed of install
- A unique 360° rotation for total flexibility, and a 180° tilt
- Suitable for coastal areas
- Performs in even more extreme conditions from -40°C to +40°C
- Supplied with 1m cable
- Wide 120° beam angle, reducing the number of fittings per area required

SIZE DIAGRAM



ACCESSORIES N/A