

FL05

50W colour switchable floodlight suitable for 15m height



Product code	Finish	Type	Wattage	Colour	Beam	lm	lm/W	lx at 1m
FL05BPCS	Black	PIR sensor	50W	3000K	120°	5000	100	2230
				4000K	120°	5600	112	2449
				6500K	120°	5100	102	2230
FL05BXCS	Black	Standard	50W	3000K	120°	5000	100	2230
				4000K	120°	5600	112	2449
				6500K	120°	5100	102	2230
FL05WPCS	White RAL9016	PIR sensor	50W	3000K	120°	5000	100	2230
				4000K	120°	5600	112	2449
				6500K	120°	5100	102	2230
FL05WXCS	White RAL9016	Standard	50W	3000K	120°	5000	100	2230
				4000K	120°	5600	112	2449
				6500K	120°	5100	102	2230
FL05APCS	Anthracite grey RAL7016	PIR sensor	50W	3000K	120°	5000	100	2230
				4000K	120°	5600	112	2449
				6500K	120°	5100	102	2230
FL05AXCS	Anthracite grey RAL7016	Standard	50W	3000K	120°	5000	100	2230
				4000K	120°	5600	112	2449
				6500K	120°	5100	102	2230

Floodlights



High efficacy of up to 112lm/W



First fix bracket for quick & easy installation



Ideal for coastal areas

Guarantee	5 years for standard & 3 years for PIR
Wattage	50W
IP rating	IP65
IK rating	IK07
Tiltable	180°
Rotatable	360°
Dimmable	No
Input	220-240V 50/60Hz
LED lifetime	50,000h L70 25,000h L70 (with PIR)
Connector	Flying lead
Ambient temperature	-40°C to 40°C
Electric class	1

