GL016RGBW

LED colour change ground light
with white LED (5W max.)

W | IP67 | IK09 | 50,000h L50,B50 | 3SDCM

Guarantee / Warranty: 5 year extended warranty available

PHOTOMETRICS @ 25°C

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx at 1m
GL016RGBW	1.2W	4000K	40°	50	42	74
	1W	Red	40°	38	38	75
	1.2W	Green	40°	63	53	124
	1.2W	Blue	40°	11	9	17

INSTALLATION INFORMATION

|	
Cut-out size	Ø50mm
Construction material	Stainless steel (316)
Weight	300g
Class	Class III
Max. ambient temperature	35°C

BENEFITS

- Installation tube available
- Low profile for easy installation
- Full RGBW colour range
- Separate white LED for permanent use
- Compatible with a large range of controllers
- Marine grade stainless steel for use in outdoor and indoor environments
- Suitable for coastal areas

SIZE DIAGRAM

Ø60mm
48mm
1m

ACCESSORIES

JB7	5-pole IP68 inline connector
TUBE/50	Installation tube
CR575RGBW	5-core PVC cable

GL050RGBW

Colour change LED ground / marker light
with white LED (5W max.)

W | IP67 | IK08 | 50,000h L50,B50 | 3SDCM

Guarantee / Warranty: 7 year extended warranty available

PHOTOMETRICS @ 25°C

Product Code	W	Colour	Beam Angle	lm	lm/W	lx at 1m
GL050RGBW	1.2W	4000K	100°	11	9	2
	1W	Red	100°	9	9	2
	1.2W	Green	100°	13	11	3
	1.2W	Blue	100°	2	2	1

INSTALLATION INFORMATION

Cut-out size	Ø65mm
Construction material	Stainless steel (316)
Weight	552g
Class	Class III
Max. ambient temperature	35°C

BENEFITS

- Frosted glass for subtle colour change
- Low profile for easy installation
- Full RGBW colour range
- Separate white LED for permanent use
- Compatible with a large range of controllers
- Marine grade stainless steel for use in outdoor and indoor environments
- Suitable for coastal areas

SIZE DIAGRAM

Ø76mm
43mm
1m

ACCESSORIES

JB7	5-pole IP68 inline connector
TUBE/68	Installation tube
CR575RGBW	5-core PVC cable
GLA01	Ground light accessory, square plate, stainless steel 316