

Ground lights

GL019

Up to 2W, 180lm mini ground light



Guarantee / Warranty: 7 year extended warranty available



Stainless steel



Antique brass



Black

PHOTOMETRICS @ 25°C

Product Code	Finish	Colour	Beam Angle	350mA			700mA		
				Wattage	lm	lm/W	Wattage	lm	lm/W
GL019 F NW	Stainless steel	4000K	38°	1W	100	100	2W	180	90
GL019 S NW	Stainless steel	4000K	12°	1W	100	100	2W	180	90
GL019 F WW	Stainless steel	3000K	38°	1W	90	90	2W	150	75
GL019 S WW	Stainless steel	3000K	12°	1W	90	90	2W	150	75
GL019 F 27	Stainless steel	2700K	38°	1W	80	80	2W	130	65
GL019 S 27	Stainless steel	2700K	12°	1W	80	80	2W	130	65
GL019 F AMBER	Stainless steel	Amber	38°	1W	20	20	2W	-	-
GL019 F BLUE	Stainless steel	Blue	38°	1W	10	10	2W	25	13
GL019 S BLUE	Stainless steel	Blue	12°	1W	10	10	2W	25	13
GL019 F RED	Stainless steel	Red	38°	1W	35	35	2W	-	-
GL019AWBX30	Antique brass	3000K	38°	1W	90	90	2W	150	75
GL019ANBX30	Antique brass	3000K	12°	1W	90	90	2W	150	75
GL019AWBX27	Antique brass	2700K	38°	1W	80	80	2W	130	65
GL019ANBX27	Antique brass	2700K	12°	1W	80	80	2W	130	65
GL019WBX40	Black	4000K	38°	1W	100	100	2W	180	90
GL019NBX40	Black	4000K	12°	1W	100	100	2W	180	90
GL019WBX30	Black	3000K	38°	1W	90	90	2W	150	75
GL019NBX30	Black	3000K	12°	1W	90	90	2W	150	75
GL019WBX27	Black	2700K	38°	1W	80	80	2W	130	65
GL019NBX27	Black	2700K	12°	1W	80	80	2W	130	65
GL019WBXBL	Black	Blue	38°	1W	10	10	2W	25	13
GL019NBXBL	Black	Blue	12°	1W	10	10	2W	25	13


INSTALLATION INFORMATION

Input	350mA / 700mA
Dimmable	Requires driver
Cut-out size	Ø33mm
Construction material	Stainless steel (316)
	Antique brass: Brass
	Black: Anodised aluminium
Weight	Stainless steel: 204g
	Antique brass: 221g
	Black: 120g
Class	Class III
Max. ambient temperature	50°C

BENEFITS

- Can be powered by either 350mA or 700mA low voltage driver depending on required light output
- Compact yet powerful fitting
- Marine-grade stainless steel 316
- Black versions are not walk-over rated
- Robust cable for outdoor use
- Shallow depth for easy installation

SIZE DIAGRAM



ACCESSORIES

JB2 / JB4 / JB6 IP68 waterproof connectors

TUBE332 Installation tube