

Technical Specification

Product Code: GM2017BKSB      Description: 20A Flex Outlet Module



General Information

|                         |                                                                                                                         |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Dimensions              | 24.5mm (W) x 50mm (H) x 28mm (D)                                                                                        |
| Aperture Dimensions     | 20mm (W) x 35mm (H)                                                                                                     |
| Module Frame Finish     | Black                                                                                                                   |
| Module Finish           | Satin Brass                                                                                                             |
| Materials               | Body & Insert: Nylon<br>Insert Cover: Stainless Steel<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated |
| Maximum Voltage         | 250V 50Hz                                                                                                               |
| Load Rating             | 20A                                                                                                                     |
| Terminal Size           | 5mmø                                                                                                                    |
| Terminal Torque         | 1.2Nm                                                                                                                   |
| Terminal Capacity       | 3 x 2.5mm <sup>2</sup> or 1 x 4mm <sup>2</sup>                                                                          |
| Flex Outlet             | Yes (10mmø Through Front of the Module)                                                                                 |
| Back Box Depth          | Dependent On Plate Used                                                                                                 |
| Operational Temperature | -5°C to +40°C                                                                                                           |
| Warranty                | 10 Years                                                                                                                |
| Standards               | BS 5733: 2010                                                                                                           |

|                        |                                                                                                                                                                                                                                            |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional Information | Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.<br>Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

UK Design Registration: 3015621