

Product Code: GM2017GYSS  
 Description: 20A Flex Outlet Module

Luckinslive 425338687



General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 28 (D)	
Finish	Stainless Steel	
Insert Colour	Grey	
Materials	Body & Insert: Nylon	Insert Cover: Stainless Steel
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5, 2 x 4	
Flex Outlet Available	Yes	
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm) Ø10
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	
Standards	BS 5733	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Patent: GB 2578427



Scolmore House, Mariner, Lichfield Road Industrial Estate,  
 Tamworth, Staffordshire, B79 7UL United Kingdom  
 T: +44 (0)1827 63454 | F: +44 (0)1827 63362  
 E: sales@scolmore.com | W: scolmore.com



Catalogue



Range



DoC



Installation

